

# ND timed solenoid drains

175 to 6000 psig



nano carries a wide range of timed solenoid condensate drains for a variety of applications. Choose from the cost effective economy drain for low or high flows, the full featured premium drain in either brass or stainless steel or high-pressure drains in brass or stainless steel for applications up to 6000 psig.



## NETD economy timed solenoid (low flow)

drain model	service kit		inlet	outlet	pressure rating	supply voltage
	part no.	NPT				
NETD 14 115	NETD MK		½" (m)	¼" (f)	230	115 V
NETD 14 230	NETD MK		½" (m)	¼" (f)	230	230 V
NETD 38 115	NETD MK		½" (m)	⅜" (f)	230	115 V
NETD 38 230	NETD MK		½" (m)	⅜" (f)	230	230 V
NETD 12 115	NETD MK		½" (m)	½" (f)	230	115 V
NETD 12 230	NETD MK		½" (m)	½" (f)	230	230 V



## NPTD premium timed solenoid (brass)

drain model	service kit		inlet	outlet	pressure rating	supply voltage
	part no.	NPT				
NPTD 12 115 B	NPTD MK		½" (m) <sup>(2)</sup>	½" (f)	230	115 V
NPTD 12 230 B	NPTD MK		½" (m) <sup>(2)</sup>	½" (f)	230	230 V
NPTD 12 24A B	NPTD MK		½" (m) <sup>(2)</sup>	½" (f)	230	24 VAC
NPTD 12 24D B	NPTD MK		½" (m) <sup>(2)</sup>	½" (f)	230	24 VDC



## NPTD premium timed solenoid (stainless steel)

drain model	service kit		inlet	outlet	pressure rating	supply voltage
	part no.	NPT				
NPTD 14 115 S	NPTD MK		¼" (f)	¼" (f)	230	115 V
NPTD 14 230 S	NPTD MK		¼" (f)	¼" (f)	230	230 V
NPTD 38 115 S	NPTD MK		⅜" (f)	⅜" (f)	230	115 V
NPTD 38 230 S	NPTD MK		⅜" (f)	⅜" (f)	230	230 V
NPTD 12 115 S	NPTD MK		½" (f)	½" (f)	230	115 V
NPTD 12 230 S	NPTD MK		½" (f)	½" (f)	230	230 V

## NHPTD high pressure timed solenoid (brass)



drain model	service kit	inlet	outlet	pressure rating	supply voltage
	part no.	NPT	NPT	psig	1ph/60Hz
NHPTD 14 115 600 B	NHPTD 600	¼" (f)	¼" (f)	600	115 V
NHPTD 14 230 600 B	NHPTD 600	¼" (f)	¼" (f)	600	230 V
NHPTD 14 115 1200 B	NHPTD 1200	¼" (f)	¼" (f)	1200	115 V
NHPTD 14 230 1200 B	NHPTD 1200	¼" (f)	¼" (f)	1200	230 V

## NHPTD high pressure timed solenoid (stainless steel)



drain model	service kit	inlet	outlet	pressure rating	supply voltage
	part no.	NPT	NPT	psig	1ph/60Hz
NHPTD 14 115 600 S	NHPTD 600	¼" (f)	¼" (f)	600	115 V
NHPTD 14 230 600 S	NHPTD 600	¼" (f)	¼" (f)	600	230 V
NHPTD 14 115 1200 S	NHPTD 1200	¼" (f)	¼" (f)	1200	115 V
NHPTD 14 230 1200 S	NHPTD 1200	¼" (f)	¼" (f)	1200	230 V
NHPTD 14 115 3625 S	NHPTD 3625	¼" (f)	¼" (f)	3625	115 V
NHPTD 14 230 3625 S	NHPTD 3625	¼" (f)	¼" (f)	3625	230 V
NHPTD 14 115 5000 S	NHPTD 5000	¼" (f)	¼" (f)	5000	115 V
NHPTD 14 230 5000 S	NHPTD 5000	¼" (f)	¼" (f)	5000	230 V
NHPTD 14 115 6000 S	NHPTD 6000	¼" (f)	¼" (f)	6000	115 V
NHPTD 14 230 6000 S	NHPTD 6000	¼" (f)	¼" (f)	6000	230 V

specifications	NETD low flow	NPTD brass	NPTD stainless	NHPTD brass	NHPTD stainless
material of construction	brass	brass	stainless	brass	stainless
isolation valve	mounted	integral	-	-	-
strainer	mounted	integral	-	-	-
timer	economy	premium	premium	premium	premium
anti air lock connector	-	-	-	-	-
6 ft power cord	included	included <sup>(3)</sup>	included	included	included



NETD & NPTD maintenance kit



NHPTD 600 & 1200 maintenance kit



NHPTD 3625 & 5000 maintenance kit



NHPTD 6000 maintenance kit

(1) quantity pricing applies to a single order for a single version of 10 or more drains  
 (2) inlet connection fits both ½" female and ¼" male threads  
 (3) 115V and 230V models only. 24V models include unwired DIN connector

# ND zero air loss condensate drains

up to 290 psig



nano carries a wide range of condensate drains for a variety of applications. Choose from timed solenoid drains, an automatic float drain, and magnetic or level controlled zero air loss drains. Drains are also available for high-pressure applications in brass or stainless steel.



## NED automatic float

drain model	inlet	outlet	pressure rating
	NPT	NPT	psig
NED 12	½" (f)	½" (f)	290



## NED-LC level controlled zero air loss

drain model	inlet	outlet	pressure rating	supply voltage	service kit <sup>(1)</sup>
	NPT	NPT	psig	1ph/60Hz	part no.
NED 4L N12 115	½" (m)	¾" (f)	230	115 V	NED4-500L
NED 8LC N12 115	½" (f) x2	¾" (f)	230	115 V	NED4-500L
NED 16LC N12 115	½" (f) x2	¾" (f)	230	115 V	NED4-500L
NED 40LC N12 115	½" (f) x2	¾" (f)	230	115 V	NED4-500L
NED 160C N12 115	½" (G) x2	¾" (f)	230	115 V	NED4-500L



## NMD magnetic and TD pneumatically operated zero air loss

drain model	inlet	outlet	pressure rating	service kit <sup>(1)</sup>
	NPT	NPT	psig	part no.
NMD 6 <sup>(1)</sup>	½" (f)	¾" (f)	230	NMD MK6
NMD 12	½" (f)	¾" (f)	230	NMD MK12
TD 3000	½" (f) x3	¼" (f)	230	TD MK

(1) the NMD 6 is a smaller, more compact version of the NMD 12 and is painted black



## NHD heated zero air loss

drain model	inlet	outlet	pressure rating	supply voltage	service kit <sup>(1)</sup>
	NPT	NPT	psig	1ph/60Hz	part no.
NHD 12	½" (f)	¼" (f)	230	115 V	NHD MK

specifications	NED	NED-LC	NMD	NHD
material of construction	aluminum	aluminum <sup>(2)</sup>	aluminum	aluminum
isolation valve	-	-	-	-
strainer	-	integral	-	integral
timer	-	-	-	-
anti air lock connector	included	-	included	-
6 ft power cord	-	included	-	included

(1) consult support@n-psi.com for service kit contents

(2) NED4L is made from glass reinforced plastic. All other NED-LC models are aluminum